

8 Port (一對七)網路交換機(Switch)模組



Specification	SES-107
Standards	<ul style="list-style-type: none"> ◆ IEEE 802.3 10Base-T Ethernet ◆ IEEE 802.3u 100Base-TX ◆ ANSI/IEEE 802.3 Nway auto recognition
Protocol	CSMA/CD
Topology	Star
Data Transfer Rate	<ul style="list-style-type: none"> ◆ Ethernet: 10Mbps half duplex; 20Mbps full duplex ◆ Fast Ethernet: 100Mbps half duplex; 200Mbps full duplex
Network Media	<ul style="list-style-type: none"> ◆ 10BaseT: 2-pair UTP Cat 3,4,5, EIA/TIA-568 100 ohm screened twisted pair(STP) ◆ 100BaseT: 2-pair UTP Cat 5, EIA/TIA-568 100 ohm screened twisted pair(STP)
LEDs	Per Device: Power
	Per Port: 10M Link/ACT; 100M Link/ACT; FDX/Collision
RAM Buffer	128Kbytes
Filtering Addr. Table	8k
Power Adapter	9V DC; 1A
Power Consumption	2W(max.)
Environment	<ul style="list-style-type: none"> ◆ Operating Temperature: 0 to 50° C ◆ Storage Temperature: -20 to 70° C ◆ Operating Humidity: 10 to 80% RH ◆ Storage Humidity: 5 to 90% RH